


# PEARL Economizer

- + ACCESSORY**  
 Outside Air Damper management for a Pelican Thermostat. (Only compatible with Pelican Thermostats: TS200, TS250, TS200H, TS250H).
- + ECONOMIZATION MANAGEMENT**  
 Combining the PEARL with a Pelican TS200 or TS200H delivers complete Internet-enabled economizer control. Pelican uses outside air temperature, supply temperature, space temperature, thermostat set point, and the demand in the space to intelligently decide when to use outside air.
- + INDOOR AIR QUALITY CONTROL**  
 The PEARL has built-in Internet Enabled fault detection and diagnostic feedback. By monitoring space, supply, and outside temperatures, and the outside damper position, the PEARL is able to send an alarm if the HVAC equipment or the outside air damper fails. Alarms are sent via email, text, and/or displayed on the Pelican Web App.
- + INSTALLATION AND CONFIGURATION**  
 The PEARL only requires three standard thermostat wires between it and a Pelican thermostat. Compatible with industry standard unshielded thermostat wiring up to 500 feet between devices. Configuration is accomplished through a single one-button calibration process. The PEARL goes through a self testing and adjustment algorithm. Adjustments of default settings are done through the Pelican Web App.
- + HISTORICAL DATA**  
 All temperatures (outside, supply, return, and conditioned space) and CO2 levels can be viewed in real-time online via the Pelican Web App. Damper position, calls for Heat, Cool, and/or Fan can also be viewed online. Two years of historical tracking of trend data is stored and viewable on online historical graphs.
- + CERTIFIED**  
 California Energy Commission Certified  
 California Title 24 Compliant  
 ASHRAE Compliant

**Designed and assembled in the USA**  
**5-Year Limited Warranty**



## Specifications

POWER	
Hardwire	24VAC; 50 mA
OUTPUTS	
(A1)	0-10VDC (Actuator)
(A2)	0-10VDC (VFD)
(E)	24VAC (Exhaust Fan)
(Y, W, G, Y2, W2)	24VAC
INPUTS	
(S1)	0-10VDC (Actuator)
(S2)	0-10VDC (Future Use)
(T1)	10K Type II (Supply Air)
(T2)	10K Type II (Return Air)
(T3)	10K Type II (Outside Air)
RANGES	
Operating Range	-20°F to 160°F
Operating Humidity (%RH)	5 to 90% RH
External Temperature Range	-20°F to 180°F
SIZE	
Inch	H 5.2 x W 3.6 x D 1.1
mm	H 63.5 x W 63.5 x D 19.05
Vertical Mounting	

Pelican Wireless Systems | 2655 Collier Canyon Road, Livermore CA 94551  
 (888) 512-0490 | sales@pelicanwireless.com