

TCM1 Wireless 24VAC Controller

The TCM1 has two primary applications:

- 1) For hotel rooms with PTAC units which currently do not have wire ran between the unit and a thermostat. Use the TCM1 to control the 24VAC PTAC unit and an RT1-DC as a battery-powered remote wireless thermostat on the wall.
- 2) Applications where there are zone dampers, but no wire running from the damper actuator to a thermostat. Use the TCM1 to control the 24VAC damper actuator and either an RT1-AC or RT1-DC remote wireless thermostat on the wall.

+ MESH WIRELESS NETWORK

The TCM1 communicates wirelessly with a GW400 to reach the Internet. Each TCM1 has built-in state-of-the-art wireless mesh network communication and repeating.

+ FAULT ALARMING

Built-in system and space analytics with automated email or text message alerts when a fault is detected.

+ WEB APP

Connecting a TCM1 to a RT1-DC or RT1-AC is done online through the Pelican Web App. Management and scheduling is also available through the Web App.

+ HISTORICAL TREND DATA

Online viewable historical data on space temperature, setpoints, HVAC demand, and fan demand.

+ INSTALLATION

The TCM1 is a 24VAC control module that can be installed directly inside a PTAC unit or at a 24VAC damper actuator. The TCM1 will control the connected devices and is configured through the Pelican Web App.

NOTE: This device cannot be installed inside of a metal rooftop HVAC unit. Metal enclosures block wireless signals.

Designed and assembled in the USA
5-Year Limited Warranty



Specifications

POWER

Hardwire:	24VAC, 60Hz; 50 mA
Voltage Range:	23 - 30VAC
Relay Current:	1.0A running

WIRING

Conventional:	R, RC, W, W2, Y, Y2, G, C
Heat Pump:	R, RC, O/B, AUX, Y, Y2, G, C
Damper Actuator:	Y/Y2 - 24VAC CONTROL W/W2 - 24VAC REHEAT

SYSTEM PROTECTION

Four-minute Compressor Short-cycle Protection
 Temporary Schedule Override
 Auxiliary/Emergency Heat Efficiency Algorithm
 Keypad Lockout
 Trend Data Analytics and Fault Monitoring

COMPATIBILITY

24VAC gas, electric, or oil heating systems.
 Conventional and Heat Pump

TCM1 RANGE

Operating Range	-4°F to 122°F
Differential Temperature	±0.5°F
Operating Humidity (%RH)	5 to 90% RH; non-condensing
Storage Temperature	-20°F to 160°F

SIZE

Inch	H 3.5 x W 5.9 x D 1.5
mm	H 89 x W 150 x D 38
Vertical Mounting	

Pelican Wireless Systems | 2655 Collier Canyon Road, Livermore CA 94551
 (888) 512-0490 | sales@pelicanwireless.com