Data Sheet / PEM-VDC



PEARL Expansion Modulate

PELICAN PEARL ADVANCED ROOFTOP CONTROLLER ACCESSORY
Adds two (2) additional modulating outputs to the PEARL
Advanced Rooftop Controller. (Only compatible when linked to a
Pelican TC Series Thermostat).

+ MODULATING COOLING MANAGEMENT

With the expansion modulate installed, the PEARL can now provide full modulating cooling management to a target discharge air temperature. The target auto-resets based on how much cooling demand the Pelican TC thermostat indicates the room has.

→ MODULATING HEATING MANAGEMENT

With the expansion modulate installed, the PEARL can now provide full modulating heating management to a target discharge air temperature. The target auto-resets based on how much heating demand the Pelican TC thermostat indicates the room has.

INSTALLATION AND CONFIGURATION

The PEARL and its expansion modulate only requires three standard thermostat wires between them and a Pelican TC thermostat. Compatible with industry standard unshielded thermostat wiring up to 500 feet between devices. Configuration is accomplished through the Pelican Connect™ web-app.

+ HISTORICAL DATA

All data points are tracked through the Pelican Connect™ webapp for full testing and confirmation of equipment operation. Two years of historical tracking of trend data is stored and viewable.

— COMMON USAGE

Modulating Compressor (1-5 VDC) Modulating Gas Burner (0-10 VDC) Modulating Chilled Water Valve (2-10 VDC) Modulating Hot Water Valve (2-10 VDC) Modulating Electric SCR Heater (0-10 VDC)

Designed and assembled in the USA 5-Year Limited Warranty



Specifications

POWER

24VAC; 20 mA

0	IJ.	Τ	Р	U	Т	C

(A3)	0-10 VDC
(A4)	0-10 VDC
(C)	VDC COMMON

3-PIN POWER & COMMUNICATION

_
1
4

RANGES

Operating Range -20°F to 160°F Operating Humidity (%RH) 5 to 90% RH

SIZE

Inch H 2.5 x W 1.25 x D 1 mm H 63.5 x W 31.75 x D 25.4

Pelican Wireless Systems | 2655 Collier Canyon Road, Livermore CA 94551 (888) 512-0490 | sales@pelicanwireless.com