### Data Sheet / PEARL



## **PEARL** Advanced Controller

#### ACCESSORY

Advanced equipment controller accessory compatible with all Pelican thermostats.

#### ECONOMIZATION MANAGEMENT

Combines with a Pelican thermostat for complete, Internetenabled economizer control. Uses outside air temperature, supply temperature, space temperature, thermostat set-point, and realtime demand to optimize ventilation and energy savings.

#### + DEMAND BASED VENTILATION AND AIR QUALITY CONTROL

When paired with a CO2 Pelican thermostat, the PEARL continuously monitors occupancy and automatically adjusts ventilation based on real-time demand. It also monitors space, supply, and outside temperatures, and damper position. Fault alarms—such as HVAC or outside air damper failures—are sent automatically via email, text, and the Pelican Web App.

#### + ADVANCED EQUIPMENT MODULATION

Provides precise control of variable frequency drives (VFDs), hot or chilled water valves, and other advanced HVAC equipment. The PEARL dynamically modulates outputs based on real-time conditions to maintain optimal performance and energy efficiency.

#### SIMPLE INSTALLATION & CONFIGURATION

Requires only three standard thermostat wires (up to 500 feet, unshielded). Features one-button calibration with automated self-testing and tuning. All settings can be adjusted via the Pelican Web App.

#### + REAL-TIME & HISTORICAL DATA

View temperatures (space, supply, return, outside), damper position, HVAC calls, and CO2 levels live Online. Access up to two years of trend data through interactive graphs.

#### + CERTIFIED FOR COMPLIANCE

- California Energy Commission Certified
- California Title 24 Compliant
- Follows ASHRAE Standards

# Designed and assembled in the USA

5-Year Limited Warranty





#### Specifications

POWER	
Hardwire	24 VAC, 60 Hz, 50 mA
OUTPUTS	
(A1)	0-10 VDC
(A2)	0-10 VDC
(E)	24 VAC, 2.0A max
INPUTS	
(S1)	0-10VDC
(S2)	0-10VDC
(T1)	10K Type II
(T2)	10K Type II
(T3)	10K Type II
RANGES	
Operating Range	-20°F to 160°F
Operating Humidity (%RH)	5 to 90% RH
External Temperature Rang	ge -20°F to 180°F
SIZE	
Inch	H 5.2 x W 3.6 x D 1.1
mm H 6	53.5 x W 63.5 x D 19.05

Pelican Wireless Systems | 2655 Collier Canyon Road, Livermore CA 94551 (888) 512-0490 | sales@pelicanwireless.com